


**QUICK GUIDE FOR
THE CREATION OF DOCUMENTS
FOR DIGITAL PRINTING**

**A WELL-SENT
DOCUMENT...
IS A SAFE
PRINTING.**

La Impremta Total 
pressing
www.pressing.es



HOW TO CORRECTLY CREATE A FILE FOR DIGITAL PRINTING

1 - FILE FORMAT

Our systems only work with PDF files in 1:1 scale (without password protection).

2 - THE COLORS


All files are sent in CMYK (cyan, magenta, yellow, black). Images in RGB or with PANTONE colors will be converted to a standard separation profile automatically.

3 - RESOLUTION

The optimal resolution of files for printing is from 250 to 300 dpi.

4 - MARGINS AND BLEEDING









The correct bleeding is 3 mm. The distance of the texts with respect to the cut line must be at least of 3 mm.



5 - ORIENTATION OF THE FORMAT

The orientation of the pages of the pdf must correspond to the one chosen in the order (horizontal or vertical). Both pages must have the same orientation. Once the pdf is saved, be careful not to turn the pages with Acrobat.

ATTENTION: For double sided printing, the sheet is rotated around its vertical axis, as, for example, when turning the pages of a book. It is important to take it into account when putting the text, also considering the orientation selected in the budget.


			 <p data-bbox="647 568 807 629">George Mc Kalin Lorem ipsum dolor sit amet.</p> <p data-bbox="663 707 798 786">Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed diam nonummy nibh euismod tincidunt ut laoreet dolore magna</p>		 <p data-bbox="1214 680 1374 741">George Mc Kalin Lorem ipsum dolor sit amet.</p> <p data-bbox="1230 524 1364 602">Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed diam nonummy nibh euismod tincidunt ut laoreet dolore magna</p>
	<p>HORIZONTAL</p>		 <p data-bbox="775 860 807 1021">George Mc Kalin Lorem ipsum dolor sit amet.</p> <p data-bbox="647 860 719 999">Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed diam nonummy nibh euismod tincidunt ut laoreet dolore magna</p>		 <p data-bbox="1206 972 1238 1133">George Mc Kalin Lorem ipsum dolor sit amet.</p> <p data-bbox="1294 999 1366 1133">Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed diam nonummy nibh euismod tincidunt ut laoreet dolore magna</p>

				 <p data-bbox="472 1532 632 1592">George Mc Kalin Lorem ipsum dolor sit amet.</p> <p data-bbox="472 1615 606 1693">Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed diam nonummy nibh euismod tincidunt ut laoreet dolore magna</p>		 <p data-bbox="1310 1644 1469 1704">George Mc Kalin Lorem ipsum dolor sit amet.</p> <p data-bbox="1342 1532 1476 1610">Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed diam nonummy nibh euismod tincidunt ut laoreet dolore magna</p>
	 <p data-bbox="687 1823 719 1984">George Mc Kalin Lorem ipsum dolor sit amet.</p> <p data-bbox="472 1823 544 1962">Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed diam nonummy nibh euismod tincidunt ut laoreet dolore magna</p>		 <p data-bbox="1190 1823 1222 1984">George Mc Kalin Lorem ipsum dolor sit amet.</p> <p data-bbox="1366 1823 1437 1962">Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed diam nonummy nibh euismod tincidunt ut laoreet dolore magna</p>			


6 - CREATING THE DOCUMENT




The ideal tools for creating documents are Adobe Illustrator and Adobe InDesign. Once the pages have been created with the final format of the work, indicate the bleed in "Adjust document".



Set the safety margins for texts:



7 - EXCLUSIVE FINISHES




If you have chosen the option UVI digital Enhancement, Gold Stamping or Silver Stamping, remember that the element that contains that exclusive printing finish, must be located separately in Scodix layers.

The element of the Scodix layer must not contain scuffs, reticles or transparencies, it must be vectorial and the Scodix color sample must be used.

The minimum printable size of the characters is 10 pt, while the minimum printable stroke is 1 pt. Remember that it is preferable not to add exclusive printing finishes in the areas of the cleft and cut, in order to avoid breakage of the varnish or laminate.



It is recommended to maintain a distance of at least 1 mm between the exclusive printing finishes and the cut and/or the lamination.

8 - COLOR SCOPE SCODIX



To define the parts of the design that will carry special finishes, we must place all these elements in their independent layer, using the Scodix color as shown in the image above.

9 - EXPORT DOCUMENT TO PDF



Once the design is finished, when stipulating the export parameters to PDF it is important:

- 1 - Resolution of 300 dpi.
- 2 - Indicate the cut marks and blood 3 mm.
- 3 - In the case of containing layers of finishes, separate in different PDF with the same generation characteristics:

A_ Artwork layer. (1 pdf of the design to print).

B_ Special printing finishes (1 pdf for each finish printing).